

## HCS-851A/02 Interpreter Booth



HCS-851A/02



HCS-851K

---

### Features

- Compliant to ISO 4043
- Odorless, antistatic, fire-retardant material
- Optimum insulation and sound absorption
- Hinged door (with observation window 0.20 m × 0.20 m), opens outwards, operates silently
- Two front windows and two side windows (high: 0.87 m); lower edge of the window: 0.79 m from booth floor
- Booth to hall (and vice versa) - sound pressure level difference: >24 dB (1 kHz)
- Reverberation time inside the booth: between 0.3 and 0.5 s (octave bands from 125 Hz to 4000 Hz, booth unoccupied)
- Ventilation system (purging 8 times per hour at least) of interpretation booth uses low-noise exhaust fan
- Internal dimensions of the booth h × w × d (cm): 200 × 160 × 160, accommodates two interpreters
- Overall dimensions of the booth h × w × d (cm): 204 × 172 × 172
- Shipping needs HCS-851K Interpreter Booth Shipping Case
  - Dimensions of HCS-851K h × w × d (cm): 110×209×75
  - Weight (incl. the booth): 297 kg

---

### Ordering Information

HCS-851A/02\_\_\_\_\_Interpreter Booth (accommodates 2 interpreters, internal dimensions is 200×160×160 cm, aluminum alloy framework convenience for disassembly, with a shipping case, total weight is 297 kg)

HCS-851K\_\_\_\_\_Interpreter Booth Shipping Case (for HCS-851A/02)

## HCS-851A/03 Interpreter Booth



HCS-851A/03



HCS-851K



HCS-851KT

### Features

- Compliant to ISO 4043
- Odorless, antistatic, fire-retardant material
- Optimum insulation and sound absorption
- Hinged door (with observation window 0.20 m × 0.20 m), opens outwards, operates silently
- Three front windows and two side windows (high: 0.87 m); lower edge of the window: 0.79 m from booth floor
- Booth to hall (and vice versa) - sound pressure level difference: >24 dB (1 kHz)
- Reverberation time inside the booth: between 0.3 and 0.5 s (octave bands from 125 Hz to 4000 Hz, booth unoccupied)
- Ventilation system (purging 8 times per hour at least) of interpretation booth uses low-noise exhaust fan
- Internal dimensions h × w × d (cm): 200×240×160, accommodates three interpreters
- Overall dimensions h × w × d (cm): 204×252×172
- Shipping needs HCS-851K and HCS-851KT Interpreter Booth Shipping Case
  - ♦ Dimensions of HCS-851K h × w × d (cm): 110×209×75
  - ♦ Dimensions of HCS-851KT h × w × d (cm): 91×215×40
  - ♦ Weight (incl. the booth): 415 kg

### Ordering Information

HCS-851A/03 Interpreter Booth (accommodates 3 interpreters, internal dimensions is 200 × 240 × 160 cm, aluminum alloy framework convenience for disassembly, with 2 shipping case, total weight is 415 kg)

HCS-851KT Interpreter Booth Shipping Case (for HCS-851A/03, HCS-851K needed)